



ZONE 2/22



IS-MP.2

The IS-MP.1 is a handheld reader for easy and efficient reading of RFID/NFC TAGs located closely together or positioned in areas that are difficult to access. The TAG information can be viewed directly on the OLED display, transferred via Bluetooth or read from the storage via USB.

› Please visit our website and you will find more detailed information, as well as an overview of compatible accessories. › i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi® is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. › © 2018 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1020MD02REV00_EN

TECHNICAL FEATURES



ATEX approval:
EX-zone 2/22
Ⓜ II 3G Ex ic IIC T4 Gc IP54
Ⓜ II 3D Ex ic IIIB T135°C
Dc IP54



IECEX approval:
EX-zone 2/22
Ex ic IIC T4 Gc IP54
Ex ic IIIB T135°C Dc IP54



vibration feedback



size:
190 x 30 x 35 mm,
weight: 125 g



up to 2.000 Bluetooth
readings



memory for
1.000 readings



Bluetooth® 4.0 LE



OLED-display



1 ... 3 cm
reading distance



RFID/NFC tag-reader*:
LF 125kHz,
LF 134,2 kHz
FDX-B + HDX,
HF und NFC 13,56 MHz,
UHF 868 MHz



* = Allows individual configuration.

FURTHER FEATURES



IP54 certified



operation range from
-20 °C to 60 °C



real-time clock



applications available
for ANDROID OS and
WIN OS

CONTENTS

IS-MP.2, USB cable, charger, quick start manual and safety instructions